

June/1994

This program was written by Alex Berenzon

As an undergraduate project

supervised by Nir Tessler

We hope this program will be useful to YOU

A. Berenzon and N. Tessler

Technion, Israel

This program uses:

One input file by the name of LAYERS.DAT

It's format is:

1.55 - The wave length in μm
3.30 0.01 1.50 c - $\text{Re}\{n\}$ $\text{Im}\{n\}$ Width[μm] Kind{c,s,q} : Of each layer
3.40 -0.01 0.10 s - ...
3.60 -0.01 0.08 q - ...
 maximum 100 layers...

One configuration file by the name layers.cfg and with the next format:

0.0001 - Real final resolution of n_{eff}
0.0001 - Imgn. final resolution of n_{eff}
200 - Number of points in output intensity plot (MAX is 500)
5 - Resolution factor of the first iteration of Real_axis (odd and ≤ 7)

two output files: INTNCTY.OUT CONFMNT.OUT

This program works as follows:

- 1) The solution for TE mode is looked for in a surface defined by $[\max(\text{Re}(n))..\min(\text{Re}(n))]X[\max(\text{Im}(n))..\max(\text{Im}(n))]$.
- 2) The method is based on the transmission transfer matrix and a solution is a peak in transmission.
If there is more than one mode you'll get a few peaks.
A true peak (solution) intensity increases with resolution.
- 3) After each iteration a 3D plot is shown with the lowest order mode marked. If you wish to solve for a different mode please use the arrows keys.
- 4) Once a mode is selected you can either press SPACE to continue or ESC to abort.
- 5) After the final resolution has been reached the mode profile is calculated and written into intencity.out
The file is made of $[x,\text{intencity},\text{Re}(n),\text{Im}(n)]$.
- 6) The effective index plus confinement factors are written into confinement.out

